

**HIGH-GROUND**  
Moving Yoke  
TECHNICAL FEATURES

VOLTAGE: 230V 50 OR 60 HZ (ON REQUEST)

POWER CONSUMPTION: 2000W  $\text{COS}\phi \geq 0,9$

WEIGHT: 67KG

CONTROL SYSTEM REQUIRED: DMX 512

TOTAL DMX CHANNELS REQUIRED: 10 (SEE THE DIAGRAM ENCLOSED)

STAND-ALONE PROGRAMMABLE BY THE DISPLAY BUTTONS IN THE BASE

8/16 BITS PAN/TILT RESOLUTION

MAX. PAN ANGLE: 540°

MAX. TILT ANGLE: 262°

PAN SPEED: 540° IN 3,2 SEC.

TILT SPEED: 262° IN 2,9 SEC.

IP RATE: 43 (WEATHERPROOF)

TYPE OF LAMP: OSRAM MaxiSharXS HTI 2000W/D10/60 AVERAGE LAMP LIFE: 750 H

LAMP LUMINOUS FLUX: 200.000 Lumens

LAMP ON/OFF: BY DMX

COLOURS: 5 + WHITE. RAINBOW EFFECT (ADJ. SPEED)

SHUTTER AND STROBO EFFECT FROM 1 TO 5 FLASHES PER SEC.

ZOOM: FROM 1,8° TO 20°

ZOOM SPEED: FROM 1,8° TO 20° IN ONE SEC.

ZOOM AT MIN. - ILLUMINANCE: 26.100 LUX AT 25MT. COVERED AREA: 0,65x0,35MT.

ZOOM AT MAX. - ILLUMINANCE: 380 LUX AT 25MT. COVERED AREA: Ø 9,5MT.

TROLLEY FAST MOUNTING: ON REQUEST

ALL DATA CAN BE MODIFIED WITHOUT NOTICE

24/09/2009