

NOVA FLOWER
Moving Yoke

TECHNICAL FEATURES

VOLTAGE: 230V 50 OR 60 HZ (ON REQUEST)

POWER CONSUMPTION: 1450W $\text{COS}\phi \geq 0,9$

WEIGHT: 65KG

CONTROL SYSTEM REQUIRED: DMX 512

TOTAL DMX CHANNELS REQUIRED: 14 (SEE THE DIAGRAM ENCLOSED)

STAND-ALONE PROGRAMMABLE BY THE DISPLAY BUTTONS IN THE BASE

8/16 BITS PAN/TILT RESOLUTION

MAX. PAN ANGLE: 540°

MAX. TILT ANGLE: 260°

PAN SPEED: 540° IN 3,2 SEC.

TILT SPEED: 260° IN 2,9 SEC.

IP RATE: 43 (WEATHERPROOF)

TYPE OF LAMP: OSRAM HTI 1200W/D7/60 AVERAGE LAMP LIFE: 750 H

LAMP LUMINOUS FLUX: 110.000 Lumens

LAMP ON/OFF: BY DMX

COLOURS: 6 + WHITE AND CMY COLOR MIXING

SHUTTER

REFLECTOR'S ROTATION SPEED ADJUSTABLE BY DMX (BOTH DIRECTIONS)

FLOWER'S BEAMS APERTURE : 40°

TROLLEY FAST MOUNTING: ON REQUEST

ALL DATA CAN BE MODIFIED WITHOUT NOTICE

12/01/2010